



## UPR Ford Billet Oil Drain Plug Installation and use 3025-09



1. Be sure the engine is cool, and you have a proper oil drain pan in place before removing the drain plug. Remove the factory drain plug by rotating the yellow plug counter clockwise. Once the oil has drained **completely**, wipe out the drain hole to remove residual oil.



2. To install the UPR Billet Oil Drain Plug, be sure the wave washer is in place and insert the drain valve so that the grooves engage the tabs inside the oil pan drain hole. **Push in firmly then rotate** the drain plug clockwise until it stops. You will feel the drain valve body engage and lock in. If you have the grooves in the valve lined up with the tangs in the oil pan, it will turn easily. If it is difficult to turn, stop, and recheck the alignment to prevent damage to the oil pan



3. To remove the drain plug, it is the opposite of the installation. **Push the drain plug *in* towards the oil pan firmly before turning** the drain plug counter clockwise. Failure to push the drain plug in towards the oil pan and / or using a wrench or other tools to turn the drain plu will result in oil pan damage.
4. When the oil is drained completely, wipe out the oil pan drain hole, and wipe excess oil off the drain valve. Inspect the O rings for any damage, and replace if necessary.

Reinstall the UPR Billet Oil Drain Valve (see step 2 if needed).

NOTE: You have to twist the UPR Oil Drain Valve until it stops, and then push in and twist to get over the tabs at the last 20% of the rotation and release to lock it in place. It cannot be removed unless you press it ***in*** firmly to allow the pockets in the slot to clear the tabs inside the oil pan. When removing, do not let the rotational force compress the spring. It has to be firmly pushed in before full rotation for proper installation, and removal must be firmly pushed in to allow the locking grooves in the UPR Speed Oil Drain Valve to clear the tabs and release.

**DO NOT** use pliers or other tools to remove or install the drain plug

*Product Liability Statement: The purchase of the product, manufactured by UPR Products Inc. completes an agreement between UPR Products Inc. and the customer. UPR Products Inc. assumes no liability for damages or injury incurred by the buyer of this product. The purchaser or user of this product is responsible for the proper disposal of any hazardous materials (oil catch can contents). The buyer has complete responsibility for the installation, use and upkeep of this product.*